



Aerospace
Systems Division

ATM
1065

PAGE I OF _____

DATE 19 Oct. 1971

STRUCTURAL ANALYSIS REPORT
LUNAR EJECTA AND METEORITE
EXPERIMENT

Prepared by:

J. H. Owens, Jr.

J. H. Owens, Jr.

Approved by:

Paul Pilon

D. L. Darkurst



Aerospace
Systems Division

Structural Analysis Report
Lunar Ejecta and Meteorite
Experiments

ATM

1065

PAGE II OF _____

DATE 19 Oct. 1971

INTRODUCTION

This report consists of the stress analysis performed to substantiate the structural integrity of the Lunar Ejecta and Meteorite Experiment. (LEAM).

The analysis is based on a breakdown of weights of the experiment components based on a total weight of 14.0 pounds from references (1) and (2). Final experiment weight deviated slightly from that assumed but not enough to significantly affect the analysis or structural performance.

Analysis loads are from references (1) and (3). Outer structure, UHT socket and attachment fittings are based on loads from reference (3). A factor of safety of 1.5 has been used to obtain ultimate loads.

In most cases, the margins of safety are high. Low margins of safety are based on conservative assumptions and a more vigorous analysis would show a higher margin. Items not shown in this report have been investigated and can be shown to have high margins of safety using defined load factors.

The LEAM structure consists of an outer box, an inner box, and an interface bracket, or flange.

The internal box or inner structure supports the sensors, electronics and radiator plate. It is directly attached to the interface flange which is mounted by astronaut removable Boyd bolts to the ALSEP structure. (Loads and analysis are shown on pages 4-10). The inner structure has ample strength throughout.

The outer structure is a fiberglass cover which houses the insulation, and is back-up structure for lunar mounting legs and deployment fittings. It is thermally isolated from the inner structure by special fiberglass clevis fittings and with titanium pins. The outer structure is critical for deployment loads and special reinforcing is added to the cover for deployment conditions. (Loads and analysis are shown on pages 11-27).

A discussion of the testing and development of mounting methods to protect the thin parylene films is given in dynamics documents.

At the back of the report is an appendix including supplementary investigations conducted as part of the structural analysis task, although not directly related to structural integrity.



Aerospace
Systems Division

Structural Analysis Report
Lunar Ejecta and Meteorite
Experiment

ATM
1065

PAGE III OF _____

DATE 19 Oct. 1971

TABLE OF CONTENTS

	Page
Title	I
Introduction	II
Table of Contents	III
References	IV
Criteria Summary	V
ALSEP Flight Mounting Loads	1
Internal Structure Diagrams	4
Interface Bracket Analysis	7
Outer Fiberglass Structure - Loads and Diagram	11
UHT Socket Detail Analysis	12
Outer Structure Clevis Fittings Analysis	14
Leg and Bracket Analysis	16
Appendices	A1
LEAM UHT Socket Design Loads	A2
Quartz Impact Plates Investigation	A8



Aerospace
Systems Division

Structural Analysis Report
Lunar Ejecta and Meteorite
Experiment

ATM
1065

PAGE IV OF _____

DATE 19 Oct. 1971

REFERENCES

- (1) AL900130 Performance and Design Requirements for Lunar Ejecta and Meteorite Experiment.
- (2) IC 314130 Interface Control Specification for Lunar Ejecta and Meteorite Experiment.
- (3) Letter No. 9783-951-009, Bendix Internal Memorandum "Force Emission Capability of Suited Astronaut".
- (4) Roark, R.J., "Formulas for Stress and Strain", McGraw Hill Book Company, Inc. 1943.
- (5) MIL-HDBK-5A, "Metallic Materials and Elements for Aerospace Vehicle Structures", Department of Defense, Washington, D.C.
- (6) MIL-HDBK-17 and 17A, "Plastic for Aerospace Vehicles", Part 1. Reinforced Plastics, Department of Defense, Washington, D.C.
- (7) Lockheed Stress Memo No. 88 "Tension Type Fittings" Lockheed Aircraft Corporation



Aerospace
Systems Division

Structural Analysis Report
Lunar Ejecta and Meteorite
Experiment

ATM
1065

PAGE V OF

DATE 19 Oct. 1971

CRITERIA SUMMARY

Analysis Conditions

1. 20 g limit load factor along each major axis acting independently
2. 30 lbs. handling load on end of UHT (Universal Handling Tool - Drawing 2338102 per Reference (3)).

Factor of Safety

$$\text{Ult Load/Limit Load} = 1.5$$

Design Weight Summary

Inner Structure and Interface Flange

Up Sensor 2.02 lbs.

East Sensor 2.03 lbs.

West Sensor .89 lbs.

Central Electronics 2.88 lbs.

Thermal Radiator & Masks .36 lbs.

Interface Flange .28 lbs.

Paint .10 lbs.

Internal Structure Assy. 1.77 lbs.

Thermal Bay Assy. .65 lbs.
10.98 lbs.

Outer Structure

Outer Housing Assembly 1.50 lbs.

UHT Pivot and Socket Assy .16 lbs.

Leg & Release Hardware .49 lbs.



Aerospace
Systems Division

Structural Analysis Report
Lunar Ejecta and Meteorite
Experiments

ATM
1065

PAGE VI OF _____

DATE 19 Oct. 1971

Outer Structure (continued)

Dust Covers & Release

Hardware .18 lbs.

Gnomon and Bubble .16 lbs.

Paint .30 lbs.

Cable .23 lbs.
3.02 lbs.

Total Weight 14.00 lbs.

PREPARED BY J.H.O
 CHECKED BY _____
 REVISED BY _____

ENGINEERING REPORT




Aerospace
Systems Division

DATE 2-8-71 PAGE 1
 REPORT No. ATM 1065
 MODEL LEAM

LUNAR EJECTA AND METEORITE EXPERIMENT

BRACKET ATTACHMENT TO ALSEP ~ MOUNTING LOADS




CONSERVATIVELY ASSUME 60% OF LOAD REACTED AT A & B.

FLIGHT ACCELERATION $n_x = 2.0$

$$ULT. n_x = 2.0 \times 1.5 = 3.0$$

PREPARED BY J.H.O.
CHECKED BY _____
REVISED BY _____

ENGINEERING REPORT

Aerospace
Systems DivisionDATE 2-8-71 PAGE 2
REPORT NO ATM 1065
MODEL LEAMLUNAR EJECTA AND METEORITE EXPERIMENTBRACKET ATTACHMENT TO ALSEP ~ MOUNTING LOADS


ASSUME 60% OF LOAD REACTED AT A & B
FLIGHT ACCELERATION $n_y = 30.0$

PREPARED BY J.H.O.

CHECKED BY _____

REVISED BY _____

ENGINEERING REPORT

Aerospace
Systems DivisionDATE 2-9-71 PAGE 3REPORT No. ATM 1065MODEL LEAMLUNAR EJECTA AND METEORITE EXPERIMENTBRACKET ATTACHMENT TO ALJEP ~ MOUNTING LOADS

ASSUME 60% OF LOAD REACTED AT B.C.

FLIGHT ACCELERATION $n_2 = 20$ ULT. $n_2 = 30$

PREPARED BY: J.H.O.

CHECKED BY:

REVISED BY:

ENGINEERING REPORT

BENDIX

AEROSPACE SYSTEMS DIVISION

DATE 12-17-70 PG. 4

REPORT ATM 106

MODEL TEAM

INITIAL STRUCTURE - THREE VIEW

REF. DVN. NO. 341928 1/2 SCALE

MATERIAL ~20E4T351





FIG. 1

PREPARED BY: J.H.O.
CHECKED BY:
REVISED BY:

ENGINEERING REPORT
BENDIX
AEROSPACE SYSTEMS DIVISION


DATE: 12-1-70 Pg. 5
REPORT: ATM 1065
MODEL: LEAH

INTERNAL STRUCTURE - MOUNTING FACES



MOUNTING FACE A

FIG. 2



ELECTRONICS
PACKAGE
WT.: 2.38 lbs

MOUNTING FACE B
(EAST SENSOR-DUAL)
FIG. 3 WT.: 2.03 LBS

PREPARED BY: J.H.O
CHECKED BY:
REVISED BY:

ENGINEERING REPORT
BENDIX
AEROSPACE SYSTEMS DIVISION

DATE: 12-2-70
REPORT: A-11265 Pg. 6
MODEL: L7AM

INTERNAL STRUCTURE - MOUNTING FACES





FIG. 4




PREPARED BY J.H.O.
CHECKED BY _____
REVISED BY _____

ENGINEERING REPORT

Bendix Aerospace
Systems DivisionDATE 5-18-71 PAGE 7
REPORT NO. ATM 1065
MODEL LEAM

LUNAR EJECTA AND METEORITE EXPERIMENT
FLANGE - INTERFACE BRACKET ~ DWG 2347721



MATERIAL

FIBERGLASS LAMINATE PER SPEC. MIL-P-25421B TYPE 2 CLASS I
GLASS FIBER BASE; TYPE III, CLASS 2 CLOTH BASE; NO. 120
MIN. NO. OF PLIES ~4

PREPARED BY J.H.O.

CHECKED BY _____

REVISED BY _____

ENGINEERING REPORT



Aerospace
Systems Division


DATE 5-21-71 PAGE 8

REPORT No. ATM 1065

MODEL LEAM

LUNAR EJECTA AND METEORITE EXPERIMENT

FLANGE ~ INTERFACE BRACKET ~ DWG. 2347721



PREPARED BY J.H.O.

CHECKED BY _____

REVISED BY _____

ENGINEERING REPORT

Aerospace
Systems DivisionDATE 5-21-71 PAGE 9REPORT NO. ATM 1065MODEL LEAMLUNAR EJECTA AND METEORITE EXPERIMENTFLANGE~INTERFACE BRACKET ~ DWG. 2347721

PT A

ANALYZE AS AN ANGLE FITTING

REF. LOCKHEED STRESS MEMO NO. 88

P = 249.4 LBS. (REF. PG. 11) HANDLING LOADS

$$M_x = \frac{P}{(a+b)} ac = \frac{249.4}{2.4} \times .60 = 62.5 \text{ IN LBS} = M_y$$

SEE PG. 8 FOR DIAGRAM

$$\sigma_b = \frac{6M}{bd^2} = \frac{6 \times 62.5}{1.2 \times .25^2} = 5000 \text{ PSI} \quad \text{M.S. AMPLE}$$

WITH HATCHED AREA REMOVED

$$M = \frac{249.4}{1.88} \times .47 = 62.5 \text{ IN LBS} \quad \sigma_b = 5000 \text{ PSI}$$

P = 147 LBS (REF. PG. 11)

$$M_x = M_y = 36.80 \text{ IN. LBS.}$$

$$\sigma_b = \frac{6M}{bd^2} = \frac{6 \times 36.8}{1.2 \times .25^2} = 2940 \text{ PSI} \quad \text{M.S. AMPLE}$$

NOTE: EDGE DISTANCES DO NOT CONFORM TO
 THOSE RECOMMENDED IN MIL HDBK 17 (REF. 6)
 OTHER SOURCES. HOWEVER AT THE LOW LOADS
 IT SEEMS THAT THESE REQUIREMENTS ARE
 INAPPLICABLE.

PREPARED BY J.H.O.
CHECKED BY _____
REVISED BY _____

ENGINEERING REPORT

Aerospace
Systems Division

DATE 5/24/71 PAGE 10
REPORT No. ATM 1065
MODEL LEAM

LUNAR EJECTA AND METEORITE EXPERIMENT
FLANGE ~ INTERFACE BRACKET ~ DWG. 2347221

PT. B

$$\sigma_{BR} = \frac{243}{188 \times 12} = 10800 \text{ PSI} \quad \text{M.S. AMPLE}$$

BENDING OF WEB a-a (HANDLING LOAD)

$$M = \frac{243 \times 1.38}{2} = 167.5$$

$$\sigma_b = \frac{6 \times 167.5}{1.25 \times 19^2} = 22200 \text{ PSI}$$

$$\sigma_{ALLOW} = 28000 \quad \text{M.S.} = \frac{28000}{22200} - 1 = 2.6$$

BENDING OF WEB b-b (LAUNCH LOAD)

$$M = 147 \times 1.1 = 162$$


$$\sigma_b = \frac{6 \times 162}{1.1 \times 19^2} = 22300 \text{ PSI} \quad \text{M.S.} = \frac{28000}{22300} - 1 = 2.6$$

$$F_b = 28000 \sim \text{CONSERVATIVE}$$




MATERIAL: FIBERGLASS LAMINATE PER MIL-P-25421 TYPE II CLASS 1
GLASS FIBERBASE - TYPE 1 CLASS 2 CLOTH BASE NO. 12
MIN. NO. OF PLIES ~ 4

NOTES: - CRITICAL CONDITION FOR FIBERGLASS DUTEX
STRUCTURE IS DEPLOYMENT LOAD APPLIED TO
SWIVEL FITTING BRACKET.
(REF 3)

DATE 10-18-71 Pg. 11
ICET-1000 N-ATM1065
PAGE 2 LEAM



MFG. FACES
FOR LEG BRACKETS
SEE DETAIL



OUTER FIBERGLASS STRUCTURE 1WV4.1541734 1/2 SCALE

PREPARED BY J.H.O.
CHECKED BY _____
REVISED BY _____

ENGINEERING REPORT

Bendix

Aerospace
Systems Division


DATE 10/12/71 PAGE 12
REPORT NO. ATM 1065
MODEL LEAM

LUNAR EJECTA AND METEORITE EXPERIMENT

SWIVEL FITTING DETAIL ~ OUTER STRUCTURE

LOADS

REF. (3)
ASSUME 30LBS (1M)
APPLIED AT END OF
UHT
OUTER STRUCT.
DWG. 2347734
(FIBERGLASS)



PIVOT &
SOCKET ASSY.
DWG. 2347985


BRACKET
PIN RETAINER
DWG. 2347788

PIN BRG ON
FIBERGLAS

$$\sigma_{BP} = \frac{1035}{.31 \times .107} = 17800 \text{ PSI M.S. AMPLG}$$

2347986
MAT. 17-4PH
PULL = 2210 LBS
M.S. = \frac{2210}{1035} - 1 = 1.14

SOCKET ANALYSIS ~ DWG. 2347931 ~ NEXT ASSEM. - 2347985



MATERIAL 7075T6

SECT. A-A
B.M. = 121.5 + 45 \times 1.8 = 1296

$$I = \frac{.90^4 - .80^4}{64\pi} = .0121 \quad \frac{D}{t} = \frac{90}{.05} = 18$$

$$F_b = \frac{1296 \times .45}{.0121} = 48000 \text{ PSI}$$

R.G = MIL-HDBK
SA

$$F_b = 1.1 \times 72000 = 79000$$

$$\text{M.S.} = \frac{79000}{48000} - 1 = .64$$

BEARING AT B-B

$$F_{br} = \frac{1875}{.18 \times .10} = 104000$$

$$F_{br} = 148000 \quad \text{M.S.} = \frac{148000}{104000} - 1 = .42$$

PREPARED BY J.H.O.

CHECKED BY _____

REVISED BY _____


ENGINEERING REPORT

Aerospace
Systems DivisionDATE 1-26-77 PAGE 13REPORT NO. ATM 1065MODEL LEAMLUNAR EJECTA AND METEORITE EXPERIMENTUHT SOCKET INSERT (REF. PAGE 1A)

DWG. 2347984

NEXT ASSEM. 2347985
LOADS REF. (3)

MATERIAL 17-4 PH H900



FOR ANALYSIS OF UHT SOCKET INTERFACE SEE ATM 071
PAGES 1-40 TO 1-45 INCL.

BEARING ON FACES B-B

$$P = \frac{1215}{.313/3} = 11620 \text{ LBS} \quad W \times .313/2 = 11620 \quad W = 74300 \text{ LBS/IN.}$$

$$\bar{\sigma}_{br} = \frac{74300}{.798} = 93200 \quad M.S. = \frac{12000.0}{93200} - 1 = .29$$

RIVETS 20613-C4 MATERIAL CRES $F_{su} = 65000 \text{ PSI}$

$$P = \frac{135}{1.2 \times 2} = 56.2 \text{ LBS} \quad M.S. \text{ AMPLE}$$

PREPARED BY J.H.O
CHECKED BY _____
REVISED BY _____

ENGINEERING REPORT




Aerospace
Systems Division

DATE 10/13/71 PAGE 14
REPORT NO. ATM 1065
MODEL LEAM

LUNAR EJECTA AND METEORITE EXPERIMENT

OUTER FIBERGLASS STRUCTURE + CLEVIS BRACKET DETAIL TO INTERFACE BRACKET (REF. PAGE 11)



CLEVIS BRACKET ANALYSIS DWG. Z347760

MATERIAL:-

FIBERGLASS LAMINATE PER-MIL-P-25241
TYPE II CLASS 1

GLASS FIBER BASE - TYPE I CLASS 2

CLOTH BASE NO. 112

SECT. B-B

$$B.M. = 36 \times 54.3 = 19.6 \text{ IN. LBS.}$$


$$\sigma_b = \frac{6 \times 19.6}{.52 \times .12^2} = 15700 \text{ PSI} \quad \text{ASSUME } F_{b0} = 25000$$

$$M.S. = \frac{25000}{15700} - 1 = .60$$

SECT. C-C


$$B.M. = 192 \times 16 = 30.6 \text{ IN LBS} \quad \sigma_b = \frac{30.6 \times 6}{.6 \times .19^2} = 8470 \text{ PSI} \quad M.S. \text{ AMPLE}$$

OTHER AREAS OBVIOUSLY SATISFACTORY.



PREPARED BY J.H.O.
CHECKED BY _____
REVISED BY _____

ENGINEERING REPORT

Aerospace
Systems DivisionDATE 10/15/77 PAGE 15
REPORT NO. ATM 1065
MODEL LEAMLUNAR EJECTA AND METEORITE EXPERIMENTOUTER FIBERGLASS STRUCTURE ~ HINGE PIN DETAIL
DWG 2347725 (REF. PAGE 11)BEARING ON INTERFACE BRACKET TAB

$$\sigma_{br} = \frac{241}{.12 \times .190} = 9250 \text{ PSI} \quad \text{M.S. AMPLE}$$


NOTE: ALL M.S.'S OBVIOUSLY HIGH

PREPARED BY J.H.O.
CHECKED BY _____
REVISED BY _____

ENGINEERING REPORT

Aerospace
Systems Division

DATE 1-19-71 PAGE 16
REPORT NO. ATM 1065
MODEL LEAM

LUNAR EJECTA AND METEORITE EXPERIMENTOUTER STRUCTURE ASSY ~ LEG & BRACKET ~ UPPER

PREPARED BY J.H.O.


CHECKED BY _____

REVISED BY _____

ENGINEERING REPORT

Aerospace
Systems DivisionDATE 1-20-71 PAGE 17REPORT NO. ATM LOG5MODEL LEAMLUNAR EJECTA & METEORITE EXPERIMENTOUTER STRUCTURE ASSY ~ LEG & BRACKET ~ UPPER

SECT. A-A



$$B.M. = 21 \times 2.85 = 59.7''$$

MATERIAL ~ FIBERGLASS

PER MIL-P-18177 TYPE GEB

$$F_b = 35000 \text{ PSI}$$

$$\alpha = 66^\circ 50'$$

$$\bar{a} = K_2 R = .224 \times .28 = .063$$

$$\theta = 113^\circ 10'$$


$$I_8 = K_4 R^4 = 135 \times .28^4 \quad \text{REF SAWE} \\ = .000832 \quad \text{WT. HDBK PG. 176}$$

$$\sigma_b = \frac{59.7 \times 217}{.000832} = 15600 \text{ psi}$$

$$M.S. = \frac{35000}{15600} - 1 = 1.24$$

SECT B-B

MATERIAL ~ FIBERGLASS PER MIL-P-18177

 $F_b = 35000 \text{ PSI}$ TYPE GEB

$$S = .0091 \quad B.M. = 21 \times 5.40 = 113.5''$$

$$\sigma_b = \frac{113.5}{.0091} = 12450 \text{ psi}$$

$$M.S. = \frac{35000}{12450} - 1 = 1.81$$

PREPARED BY J.H.O.
 CHECKED BY _____
 REVISED BY _____

ENGINEERING REPORT




Aerospace
Systems Division

DATE 1-20-71 PAGE 18
 REPORT NO. ATM 1065
 MODEL LEAM

LUNAR EJECTA & METEORITE EXPERIMENT

OUTER STRUCTURE ASSY. ~ CLEVIS FITTING - UPPER

DWG NO. 234778G



SECT. A-A

$$A = .0597 \quad I = .00334$$

$$B.M. = 113.5 + 21 \times 40 \times .707 = 113.5 + 5.9 \approx 119.4$$

$$S_b = \frac{119.4 \times 353}{.00334} = 12620 \text{ lb/in}^2 \quad F_b = 1.2 \times 42000 = 50300$$

REF. MIL-HDBK 5A

$$M.S. = \frac{50300}{12620} - 1 = 2.99$$

PREPARED BY J.H.O.
CHECKED BY _____
REVISED BY _____

ENGINEERING REPORT


Aerospace
Systems Division

DATE 1-20-71 PAGE 19
REPORT NO. ATM 1065
MODEL LEAM

LUNAR EJECTA & METEORITE EXPERIMENTOUTER STRUCTURE ASSY. ~ CLEVIS FITS - UPPER

SECT. B-B

$$B.M. = 235 \times .55 = 129.5$$



$$\sigma_b = \frac{6 \times 129.5}{.12 \times 2 \times .75}^2 = 5750 \text{#/in.}$$

M.S. = AMPLE

PIN BEARING

$$\sigma_{br} = \frac{235}{.12 \times 2 \times .397} = 2460 \text{#/in.} \quad M.S. \text{ AMPLE}$$

PREPARED BY J.H.O.
CHECKED BY _____
REVISED BY _____

ENGINEERING REPORT

Aerospace
Systems DivisionDATE 1-19-71 PAGE 20
REPORT NO. ATM 1065
MODEL LEAMLUNAR EJECTA AND METEORITE EXPERIMENTOUTER STRUCTURE ASSY. ~LEG & BRACKET~LOWER

DWGS. 2347799

2347797

CONSERVATIVELY ASSUME $\frac{1}{2}$ WT.
OF EXP'MT. AT 3g ULT. ON
ONE LEG

258.5"

x 381"

35

$$P = 15 \times 3 \times .5 = 22.5^{\text{#}}$$

14.7

TUBE ANALYSIS-SECT A-A

$$B.M. = 22.5 \times 5.25 = 118.5 \text{ IN. LBS.}$$


5/8 x .035 FIBERGLASS TUBE S=.0091

PERMIL-P-18177 TYPE GEB

$$F_b = 35000 \text{ PSI}$$

$$\sigma_b = \frac{118.5}{.0091} = 13000 \text{ PSI}$$

$$M.S. = \frac{35000}{13000} - 1 = 1.69$$



PREPARED BY J.H.O.
CHECKED BY _____
REVISED BY _____



ENGINEERING REPORT

Aerospace
Systems Division

DATE 1-19-71 PAGE 21
REPORT No. ATM 1065
MODEL LEAM

LUNAR EJECTA & METEORITE EXPERIMENTOUTER STRUCTURE ASSY. ~ CLEVIS FITTING - LOWER

Dwg. 2347797



PREPARED BY J.H.O.
CHECKED BY _____
REVISED BY _____

ENGINEERING REPORT




Aerospace
Systems Division

DATE 1-19-71 PAGE 22
REPORT NO. AFM 1065
MODEL LEAM

LUNAR EJECTA & METEORITE EXPERIMENT

OUTER STRUCTURE ASSY - CLEVIS FITTING - LOWER

SECT. B-B



$$A = \left(\frac{(.705)}{2} \right)^2 - \left(\frac{(.650)}{2} \right)^2 \pi \\ = (1245 - 1055) \pi = .0597$$

$$I = \left[\frac{.705^4}{64} - \frac{.650^4}{64} \right] \frac{1}{64} \pi$$

$$= [247 - 179] \frac{\pi}{64} = .00334$$


$$\frac{D}{t} = \frac{.705}{.10275} = 25.6$$

$$B.M. = 118.5 + 22.5 \times .707 \times 40 = 118.5 + 6.4 = 124.9$$

$$\sigma_b = \frac{124.9 \times .353}{.00334} = 13100 \text{ #/in}^2 \quad F_b = 1.2 \times 42000 = 50300$$

$$M.S. = \frac{50300}{13100} - 1 = 2.75$$

SECT. C-C



$$B.M. = 118.5 + 22.5 \times .707 \times 63 \\ = 118.5 + 10 = 128.5$$

$$\sigma_b = \frac{6 \times 128.5}{.12 \times 2 \times .97^2} = 3420 \text{ #/in}^2$$

M.S. = AMPLE

PREPARED BY J.H.O.
CHECKED BY _____
REVISED BY _____

ENGINEERING REPORT

Aerospace
Systems Division

DATE 1-19-71 PAGE 23
REPORT NO. ATM 1065
MODEL LEAM

LUNAR EJECTA AND METEORITE EXPERIMENT

OUTER STRUCTURE ASSY. ~ CLEVIS FITTING - LOWER

PIN BEARING

$$\sigma_{br} = \frac{381}{.12 \times 2 \times .313} = 5100 \text{ %} \quad M.S. = \text{AMPLE}$$

TENSION AT D-D

$$M = 118.5 + 22.5 \times .707 \times .9 = 118.5 + 14.3 = 132.8 \text{ "}"$$

$$\sigma_t = \frac{132.8}{.6 \times .12 \times 2 \times .201} = 4580 \text{ %} \quad M.S. = \text{AMPLE}$$

PREPARED BY J.H.O.
CHECKED BY _____
REVISED BY _____


ENGINEERING REPORT
Bendix
Aerospace
Systems Division

DATE 5-26-71 PAGE 24
REPORT No. ATM 1065
MODEL LEAM

LUNAR EJECTA & METEORITE EXPERIMENT
LEG, PIVOT BRACKET, & BACK-UP STRUCTURE

INVESTIGATION OF DEPLOYMENT WITH 1.375 IN LBS
STORED ENERGY.

CONSERVATIVELY ASSUME ALL ENERGY TRANSFERRED
TO LEG IN FORM OF STRAIN ENERGY FROM PIVOT SPRING



SPRING DATA (REVISED)
REF. DWG. 2347796

1.325 IN LBS AT 280° DEFL.

WIRE DIA .040

.688 IN LBS AT 135° DEFL.


STOWED ENERGY AT 280° DEFL.

$$1.325 \times 3.14 \times \frac{280}{360} = 3.01 \text{ IN LBS}$$

STOWED ENERGY AT 135° DEFL.

$$= 1.325 \times 3.14 \times \frac{135}{360} = 1.55 \text{ IN LBS}$$

ENERGY EXPENDED = 1.46 IN LBS.



PREPARED BY J. HO.
CHECKED BY _____
REVISED BY _____

ENGINEERING REPORT



Aerospace
Systems Division

DATE 10/18/71 PAGE 25
REPORT NO. ATM 1065
MODEL LEM

LUNAR EJECTA & METEORITE EXPERIMENT LEG, PIVOT BRACKET, ETC (CONT'D)

STRAIN ENERGY OF A BEAM IN BENDING

$$U = \frac{1}{2} \int_0^L EI [W''(x)]^2 dx$$

WHERE $W(x)$ = DEFLECTION

U = STRAIN ENERGY

ASSUME $W(x) = \frac{W_0 x^2}{2EI} (x^2 + GL^2 - 4Lx)$

(UNIFORMLY LOAD BEAM)

$$\therefore W''(x) = \frac{W_0}{2EI} (x-L)^2$$

$$\text{so, } U = \frac{W_0^2}{8EI} \int_0^L (x-L)^4 dx = \frac{W_0^2 L^5}{40EI}$$

$$\text{THEN : } W_0 = \sqrt{\frac{40UEI}{L^5}}$$

FIND MAX STRESS DUE TO BENDING :

$$\sigma = \frac{Mc}{I}$$

$$\text{Max } M = \frac{W_0 L^2}{2} (\text{AT BASE})$$

$$\sigma_{\text{max}} = \frac{1}{2} \sqrt{\frac{40UE}{IL}}$$

$$U = 1.375 \text{ INK}$$

$$I = 2.8 \times 10^{-3} \text{ IN}^4$$

$$L = .3125 \text{ IN}$$

$$E = 2.9 \times 10^6 \text{ psi}$$

PREPARED BY J. H. O
 CHECKED BY _____
 REVISED BY _____

ENGINEERING REPORT



Aerospace
Systems Division

DATE 10/18/76 PAGE 26
 REPORT NO. ATM 1065
 MODEL LEAM

LUNAR EJECTA & METEORITE EXPERIMENT LEG, PIVOT BRACKET, ETC (CONT'D)

$$\sigma_{max} = \frac{3125}{2} \sqrt{\frac{40(1.375)(2.9) \times 10^6}{2.8 \times 10^{-3} (8)}}$$

$$f_b = \sigma_{max} = 13,200 \text{ psi}$$

$$F_b = 22,000 \text{ psi} \quad S.F. = \frac{F_b}{f_b} = 1.67$$

FOR CHANGE OF σ TO 1.46 in/k/spring (2 SPRINGS)

$$f_b = 13200 \sqrt{\frac{1.46(2)}{1.375}} = 19,100 \text{ psi}$$

FOR CHANGE TO 2024 ALUM ALLOY TUBING :

$$\frac{D}{t} = \frac{.625}{.035} = 17.8 \quad \frac{F_b}{F_{eu}} = 1.1 \quad (\text{REF MIL HDBK 5A : } \\ \text{SEI 3.9.1.1})$$

$$F_b = 64,000 \times 1.1 = 70,500 \text{ psi}$$

$\Delta E's$:

$$F_b = 70,500 \times \frac{3.2 \times 10^6}{10.7 \times 10^6} = 21,000 \text{ psi}$$


$$\therefore M.S. = \frac{21000}{19,100} - 1 = 0.10$$

PREPARED BY J.H.O.
CHECKED BY _____
REVISED BY _____

ENGINEERING REPORT


Aerospace
Systems Division

DATE 1-20-71 PAGE 27
REPORT NO. ATM 1065
MODEL LEM

LUNAR EJECTA & METEORITE EXPERIMENTLEG ATTACHMENT TO PIVOT BRACKET DETAIL

$$R_A = \frac{376}{1.046} \times 353 = 1271$$

SHAFT
(OTHER DETAILS R_B = 374 - 226 = 148)
(NOT SHOWN)



NOTE:-

ALL MARGINS OF
SAFETY ARE HIGH ON
THIS FITTING AND NO
ANALYSIS IS SHOWN

MATERIAL:

2024T4 AL. ALLOY



**Aerospace
systems Division**

Structural Analysis Report
Luncar Ejecta and Meteorite
Experiment

RECEIVED
ATM
1065

PAGE A1 OF _____

DATE 19 Oct. 1971

APPENDIX

This appendix includes items not directly connected with structural integrity of the LEAM experiment, but reports of work conducted by the Engineering Mechanics Group to assure satisfactory transportation, deployment, and operation of the LEAM experiment.

The studies consist of the following:

- (1) An investigation of socket design and deployment loads together with a recommended method of release to ensure quick and efficient deployment of the experiment.
- (2) An investigation of the quartz impact plates as to possible causes of cracks, and recommendations as to what could be done to alleviate the situation.



Aerospace
Systems Division

Structural Analysis Report
Lunar Ejecta and Meteorite
Experiment

ATM
1065

A

PAGE A2 OF _____

DATE 19 Oct. 1971

22 June 1971

Reference: 71-210-402

To: P. Pilon

From: J. H. Owens, Jr.

Subject: LEAM UHT Socket Design Loads

References:

- (1) ALSEP Array E CDR 15 - 18 June 1971 Chit No. LEAM-CDR-1
LEAM UHT Socket
- (2) "Force Emission Capability of the Suited Astronaut", Letter
No. 9783-951-009, A. J. Micocci to J. Owens 4/14/71
- (3) "Mechanical Engineers Handbok", 4th Edition, Lionel S. Marks,
Editor; McGraw-Hill
- (4) California Testing Laboratories, Inc., Los Angeles, California
Tension Tests of Ball-Lok Quick Release Pins.

This memorandum is in answer to the second part of reference (1) which states that "BxA shall provide MSC with UHT Socket Design Loads". In defining "design loads", it should be emphasized that there are three separate sets of loads with which we should concern ourselves.

(a) Operational loads: These are the loads which the astronaut must use to deploy the experiment. These are based on the normal operating forces. Every effort is made to keep the applied loads which the astronaut must exert well within his capabilities. (Pages A4-A6)

(b) Limit and Ultimate Design Handling Loads: These are the maximum loads the astronaut can apply on the handle of the UHT tool (Ref. 2). Limit loads are the loads from Ref. 2. Ultimate loads are for failure analysis and include an additional 1.5 factor of safety.

(c) Flight loads: These are the loads experienced during launch, boost and lunar descent, and are small for the socket.

In the existing design, release pin deployment loads have been drastically reduced from the DVT by changing the position of the quick release pin so that when the ball locks are released the unbalanced moment of the experiment weight causes the experiment to rotate while the astronaut supports the experiment with the UHT. This is shown in Figure 1. Further details of this release



Aerospace
Systems Division

Structural Analysis Report
Lunar Ejecta and Meteorite
Experiments

ATM
1065

PAGE A 3 OF _____

DATE 19 Oct. 1971

system are shown in detail A and section A-A on pages following Figure 1.

The following additional features of the design are emphasized:

- (1) The moment arm between separation point C and pivot point B has been approximately doubled thus reducing separation force.
- (2) The pin axis is normal to the radius BC so that separation faces release freely.
- (3) The pin has been mounted on the inner side of the socket in approximate alignment with the lateral C.G. This should eliminate any possible lateral moment on the pin.
- (4) A pin retainer mounted on the experiment housing has the pin hole countersunk to give a better bearing face for the pin balls. This results in a force component tending to push the balls toward the center of the pin, making separation more positive at release. This was done after consultation with the pin manufacturer.
- (5) The pin hole has been elongated in the vertical direction to eliminate some sliding friction on the retainer. With this it was necessary to insure that balls were horizontal by providing a non-rotating feature on the pin handle.

With this design, upon applying force to the pull pin ring, the experiment should rotate freely. The manufacturer states the necessary spring force on the ring for release to be 3 to 5 pounds. This will increase slightly to overcome ball bearing forces as shown by the friction calculations included on the page with Section A-A. In flight the only force on this pin is the very slight unbalanced force of the socket. The writer has test data showing this pin having a tension strength of 500 pounds. (Ref. 4).

Figure 2 are diagrams showing the ultimate loads used for stress analysis of the socket. Detail analysis of these parts will be included in the final stress analysis.

J. H. Owens Jr.
J. H. Owens, Jr.

EXPERIMENT OUTLINE




FIG. 1

PREPARED BY J.H.Q
CHECKED BY _____
REVISED BY _____

ENGINEERING REPORT
Bendix Aerospace Systems Division

LUNAR EJECTA AND METEORITE EXPERIMENT
EXPERIMENT DEPLOYMENT LOADS


DATE 6-21-71 PAGE A4
REPORT NO. ATK 11065
MODEL LEM

PREPARED BY J.H.O.
CHECKED BY _____
REVISED BY _____

ENGINEERING REPORT
Bendix Aerospace Systems Division

DATE 6-21-71 PAGE A5
REPORT No. ATM 1065
MODEL LEAM


LUNAR EJECTA AND METEORITE EXPERIMENT
EXPERIMENT DEPLOYMENT LOADS ON SOCKET



DETAIL A - SCALE 2/1

VIEW LOOKING OUTBOARD

Bx.A.542



15ECT. A-A~SCALE 10/1

PIN RETAINER DWG. 2347788

$$F_{\text{MAX}} = 5 \text{ LBS} + 2 \times 39.5 \times 4 = 5 + .42 = 5.42 \text{ LBS.}$$

μ : COEFF. OF ROLLING FRICTION = .003 (VERY CONSERVATIVE)
REF MARKS' HANDBOOK (REF. 3)

PREPARED BY J.H.O.
CHECKED BY _____
REVISED BY _____

ENGINEERING REPORT

Bendix
Aerospace
Systems Division

LUNAR EJECTA AND METEORITE EXPERIMENT
EXPERIMENT DEPLOYMENT LOADS ON SOCKET

DATE 6-21-71 PAGE 16
REPORT NO. ATM 1065
MODEL LEAM

PREPARED BY J.H.O
CHECKED BY _____
REVISED BY _____

ENGINEERING REPORT



Bendix

Aerospace Systems Division

DATE 6-21-71 PAGE A.7
REPORT No. ATM 1065
MODEL LEAM

LUNAR EJECTA AND METEORITE EXPERIMENT

ULTIMATE DESIGN AND ANALYSIS LOADS ON SOCKET



COND I.

COND. II

LOADS SHOWN ARE BASED ON REC. (3)

FIG. 2



Aerospace
Systems Division

Structural Analysis Report
Lunar Ejecta and Meteorite
Experiment

ATM

1065

PAGE A8 OF _____

DATE 19 Oct. 1971

To: Paul Pilon, L. Galan Informal Memorandum

From: J. H. Owens, Jr.

Subject: Results of Investigation of Cracks and Fracture of LEAM Quartz
Impact Plates

References:

- (1) Roark, R. J. "Formulas for Stress and Strain", McGraw Hill
- (2) MIL-HDBK-17A "Plastics for Aerospace Vehicles", Dept. of Defense.
- (3) Oklahoma State University ERB No. 118 "Analysis of Flat Plates by the Algebra Carry Over Method"
- (4) Corning Glass Works, Inc. "Engineering with Glass".
- (5) MIL-HDBK-722 (MR) "Military Standardization Handbook - Glass"
- (6) Machine Design July 22, 1971, "What is Fracture Mechanics".

The writer has been investigating the problem of cracks on the LEAM quartz impact plates. From ref (4) he has found that the glass used, (7940 fused silica) is a glass with a very low coefficient of thermal expansion and is used particularly for applications where a wide temperature range is anticipated. The cracks should not be due to anything inherent in the glass due to temperature variations.

However it does appear possible that stresses of a small magnitude could be built up in the glass under the epoxy bond due to differences in thermal expansion of the glass and the bond. An investigation of bonding materials might show a more desirable bonding agent.

Handling appears more likely to have caused the cracks. A small load at the top of the crystal (.6" off the plate) could induce stresses of around 10000 psi in the plate. This is high for glass.

Glass does not behave like structural materials and normal analysis procedures should be used with care. The writer would like to quote some pertinent paragraphs from Reference (5)



Aerospace
Systems Division

Structural Analysis Report
Lunar Ejecta and Meteorite
Experiment

ATM
1065

PAGE A9 OF _____

DATE 19 Oct. 1971

"17. Strength. ----- Fracture originates at a flaw and the nominal strength of the glass is determined by the severity of this flaw. In commercial glassware the weakening flaws are of accidental origin and vary greatly in severity from piece to piece in the same group, consequently there are wide variances in measured values of their breaking stress; -----

Reference (5) also states that data corresponding to other structural materials cannot be compiled for glass; being brittle, there is no yield point, elongation, or reduction of area. "Breaking stress is not an explicit function of composition but of workmanship, that is, the severity of flaw in the particular components under consideration."

"Variances of strength are not only wide, but differ from one product to another. There is no fixed relationship between average and minimum values, so that the minimum breaking stress must be determined individually for each case considered".

From the above it is apparent that confidence cannot be placed in glass that can be placed in accepted structural materials. With this memo the writer has also included a curve from ref. (6) showing effect on stress of minute cracks in a brittle material.

The writer makes the following recommendations:

1. Support impact plate on an energy absorbing material such as foam, to the extent possible, to reduce stresses in the plate to a minimum.
2. Use best available glass.
3. Have a procedure for mounting crystal, wiring, etc., that prevents rough handling of plate.
4. Carefully inspect glass microscopically in area of mounting crystal and reject those plates with minute cracks.

J. H. Owens Jr.
J. H. Owens, Jr.

PREPARED BY J.H.O.
CHECKED BY _____
REVISED BY _____

ENGINEERING REPORT




Aerospace
Systems Division

DATE 9/17/71 PAGE A10
REPORT NO. ATM 1065
MODEL LEAM

LUNAR EJECTA AND METEORITE EXPERIMENT

IMPACT PLATE INVESTIGATION

CALCULATED STRESSES & DEFLECTIONS BY CONVENTIONAL
STRESS ANALYSIS PROCEDURES FOR MAX. FLIGHT LOAD.



QUARTZ PL. T = .031
DWG 2347912

MICROPHONE CRYSTAL

DWG 2347951

DENSITY = 7.6 g/cm³

= .275 LBS/IN³

$$WT. = \frac{.6 \times .25^2}{4} \times 3.14 \times .275$$

$$= .0081$$

ASSUME 30 g - DETERMINE STRESS AT CENTER OF PLATE
USING TABLE X - ROARK - "FORMULAS FOR STRESS & STRAIN"

CASE 81

$$m = \frac{l}{D} = \frac{1}{.16} = 6.25$$

$$\sigma = \frac{3W}{2\pi mt^2} \left[\log \frac{a}{2r_0} (m+1) + .75m \right]$$

$$= \frac{3 \times 30 \times .0081 \times 10^4}{6.28 \times 6.25 \times 9.6} \left[\log \frac{4.6}{.25} (7.25) + 4.69 \right]$$

$$19.3 [2.9124 \times 7.25 + 4.69] = \underline{\underline{490 \text{ PSI}}} \quad (\text{NEGLECTING WT. OF QUARTZ})$$

ASSUME GALLOW = 10000 PSI (REF. CORNING GLASS HDBK)

$$M.S. = \frac{10000}{490} - 1 = 19.4$$

PREPARED BY J.H.O
CHECKED BY _____
REVISED BY _____

ENGINEERING REPORT



Aerospace
Systems Division

DATE 9/17/71 PAGE ALL
REPORT NO. ATM 1065
MODEL LEAM

LUNAR EJECTA AND METEORITE EXPERIMENT

IMPACT PLATE INVESTIGATION

CALCULATED STRESSES AND DEFLECTIONS BY CONVENTIONAL
STRESS ANALYSIS PROCEDURES (CONTINUED)

DEFLECTION


$$y = -\frac{.1391 Wa^2(m^2-1)}{m^2 Et^3} : -\frac{.1391 \times 30 \times .0081 \times 4.6^2(6.25^2-1)}{6.25^2 \times 10.5 \times 10^6 \times 3.1 \times 10^6}$$

$$= .0069 \text{ ULT.}$$

$$.0046" \text{ LIM.}$$

DETERMINE MAX. LOAD ON SIDE OF CRYSTAL
BEFORE IMMINENT CRACKING.

USE OKLAHOMA STATE UNIVERSITY BULLETIN NO. 118




$$Q = .394 - .043 = .351$$

$$M = .351 \times .39 P = .137 P \text{ IN LBS / IN}$$

$$G_{ALLOW} = 10000 \text{ PSI}$$

$$\frac{6 \times .137 P}{.031^2} = 10000$$

$$\therefore P = 11.6 \text{ LBS}$$



THIS IS AN APPROXIMATE
VALUE. IT IS MARKEDLY
AFFECTED BY THE
NATURE OF THE SURFACE
IN THE VICINITY OF THE
CRACK.

PREPARED BY J.H.Q
 CHECKED BY _____
 REVISED BY _____

ENGINEERING REPORT



Aerospace
Systems Division

DATE 9/17/71 PAGE A12
 REPORT NO. ATM 1065
 MODEL LEAM

LUNAR EJECTA AND METEORITE EXPERIMENT IMPACT PLATE INVESTIGATION

THERMAL EFFECTS

$$\text{ASSUME A QUARTZ PLATE .031" THICK } \Delta T = 200^{\circ}\text{F}$$

$$L_0 = 4.6" \quad \alpha = 7 \times 10^{-7} \text{ IN/IN/}^{\circ}\text{C} = 7 \times 5/9 \times 10^{-7} \text{ IN/IN/}^{\circ}\text{F} =$$

$$= 3.88 \times 10^{-7} \text{ IN/IN/}^{\circ}\text{F}$$

$$L_{200} = 4.6 + 3.88 \times 10^{-7} \times 200 \times 4.6$$

$$= 4.6 + 3580 \times 10^{-7}$$

DETERMINE R & Θ

$$4.6 = (R - \frac{.031}{2}) \Theta$$

$$4.6 + 3580 \times 10^{-7} = (R + \frac{.031}{2}) \Theta$$

$$\frac{4.6}{R - .0155} = \frac{4.6 + 3580 \times 10^{-7}}{R + .0155}$$

$$4.6R + 4.6(.0155) = 4.6R + (3580 \times 10^{-7})R - .0155 \times 4.6$$

$$+ (-.0155)(3580 \times 10^{-7})$$

$$(-3580 \times 10^{-7})R = -.14260 - 5549 \times 10^{-7}$$

$$R = 398.3"$$

ASSUME FOR A LENGTH OF .25" PL. IS RESTRAINED
FROM MOVEMENT

$$3.88 \times 10^{-7} \times .25 \times 200.0 = \frac{6}{10.5 \times 10^6} \times .25$$

$$\sigma = 3.88 \times 10^{-1} \times 200 \times 10.5$$

$$\sigma = 815 \text{ PSI}$$

PREPARED BY J. H. O
 CHECKED BY _____
 REVISED BY _____

ENGINEERING REPORT
 Bendix Aerospace Systems Division

DATE 9/23/71 PAGE A13
 REPORT NO. ATM 1065
 MODEL LEAM

LUNAR EJECTA AND METEORITE EXPERIMENT
IMPACT PLATE INVESTIGATION

THERMAL EFFECTS

EVALUATE EFFECT OF EPOXY AND GLASS PLATE WITH AT =
 200° TEMPERATURE CHANGE

$$\begin{aligned} \alpha_{\text{EPOXY}} &= 3.9 \times 10^{-6} \text{ in/in/}^{\circ}\text{F} \\ E &= 4.6 \times 10^5 \end{aligned} \quad \left. \begin{array}{l} \text{REF (2) MIL-HDBK17A} \\ \text{} \end{array} \right\}$$

$$\begin{aligned} \alpha_{\text{GLASS}} &= .388 \times 10^{-6} \text{ in/in/}^{\circ}\text{F} \\ E_{\text{GLASS}} &= 10.5 \times 10^6 \end{aligned} \quad \left. \begin{array}{l} \text{REF. CORNING GLASS} \\ \text{HANDBOOK} \end{array} \right\}$$

ASSUME STRAIN & LOADS EQUAL

$$\epsilon_{\text{GLASS}} = .031 \quad \epsilon_{\text{EPOXY}} = .010$$

$$\epsilon_g \times .031 = \epsilon_e \times .010 \quad \epsilon_e = 3.15 \epsilon_g$$

$$\alpha_e \Delta T + \frac{\epsilon_e}{E_e} = \alpha_g \Delta T + \frac{\epsilon_g}{E_g}$$

$$3.9 \times 10^{-6} \times 200 - \frac{3.15 \epsilon_g}{4.6 \times 10^5} = .388 \times 10^{-6} \times 200 + \frac{\epsilon_g}{10.5 \times 10^6}$$

$$38.6 \times 200 \times 10^{-6} = \frac{1}{10^6} (4.72 + 0.952) \epsilon_g$$

$$\epsilon_g = \underline{1165 \text{ PSI}}$$

NOTE: THIS SHOWS THAT, MAKING CONSERVATIVE ASSUMPTIONS, STRESSES IN THE GLASS REMAIN SMALL WITH CHANGES IN TEMPERATURE.

