

### LAB SIMULATION OF INTERSTELLAR DUST: A NEW APPROACH FOR HYPERVELOCITY IMPACT STUDIES

F. Postberg<sup>1,2</sup>, M. Trieloff<sup>1</sup>, R. Srama<sup>2</sup>, J.K. Hillier<sup>3</sup>, Z. Gainsforth<sup>4</sup>, A. J. Westphal<sup>4</sup>, S. Bugiel<sup>2</sup>, E. Grün<sup>2</sup>, S. Armes<sup>5</sup>, A. Kearsley<sup>6</sup>, T. Tyliczak<sup>7</sup>, W.H. Schwarz<sup>1</sup>. <sup>1</sup>Institut für Geowissenschaften, Ruprecht-Karls-Universität Heidelberg, 69120 Heidelberg, Germany. E-mail: frank.postberg@mpi-hd.mpg.de. <sup>2</sup>Max-Planck-Institut für Kernphysik, D-69117 Heidelberg, Germany <sup>3</sup>PSSRI, Open University, Milton Keynes, MK7 6AA, UK. <sup>4</sup>Space Sciences Laboratory, U. C. Berkeley, USA. <sup>5</sup>Dept. of Chemistry University of Sheffield, Sheffield, S3 7HF, UK <sup>6</sup>IARC, Dept. of Mineralogy, The Natural History Museum, UK. <sup>7</sup>Advanced Light Source, Lawrence Berkeley Laboratory, USA.

The goal of our work is the laboratory simulation of high speed [3 - 40km/s] cometary, interplanetary or interstellar dust impacts onto collector material (e.g. aerogel or foils used for the Stardust Mission). This enables an investigation of the morphology of impact tracks as well as structural and chemical modification of projectile and collector material.

**Method:** The preparation for shots on Stardust collectors [1] requires complete control of particle size and speed over a wide dynamic range. Particle speeds up to 50 km/sec can only be achieved by a Van de Graaff accelerator as, for example, operated at the MPI für Kernphysik (Heidelberg) [2]. Using an improved new version of the Particle Selection Unit, individual shots with defined speed and particle size can be performed. The experiments can be carried out using a variety of cosmochemically relevant materials (silicates, sulfides, oxides, carbides) and can provide a clear advantage over shots with a light gas gun. For use in the electrostatic accelerator these mineral grains [~ 0.1 – 5µm in size] are coated by a thin conductive layer of either platinum [3] or polypyrrole [4].

**Results:** After preliminary shots into Stardust flight spare tiles and subsequent extraction in picokeystones the suitability of this method was demonstrated in 2009 [5]. A major campaign started in spring 2010 with the goal to characterize impacts of interstellar grains. Different materials are shot within several narrow speed and size windows (e.g. 14 - 16 km/s, 0.37 – 0.43µm). For each set of parameters about 50 particles are collected. Subsequently the aerogel tiles are investigated with appropriate analytical methods (e.g. Scanning Transmission X-ray Microscopy [6]) to obtain information on track morphology and chemical alteration of grains and collector material. At a later stage the experiments will be repeated with Stardust and Genesis collector foils.

Furthermore, impact signals and impact ionisation TOF mass spectra were evaluated using the LAMA lab model [7]. These spectra provide a mass resolution of about 200 and allow determination of mineral compounds and isotopes in individual grains [8]. This type of in-situ space instrument is complementary to the collector technique and has already proven its value with the TOF - mass spectrometer onboard CASSINI [9].

**References:** [1] Westphal A. J. et al. 2009. *Lunar Planetary Science Conference 40<sup>th</sup>*: #1786. [2] Stübiger et al., *Planet. Space Sci.* 49/8, 853, 2001. [3] Hillier J. et al., *Planet. Space Sci.*, 2009. [4] Armes et al. *Polymer* 32, 2325, 1991. [5] Westphal A. J. et al. 2004 *Meteoritics & Planetary Science* 39: 175. [6] Butterworth A. L. et al. 2008 *Geochimica Cosmochimica Acta* 72: 125. [7] Srama R. et al. 2005. *ESA-Proceedings*, ESA SP-587, 171. [8] Hillier J.K et al. 2010, in prep. [9] Postberg et al. 2009, *Nature* 459, 1098-1101.